

jsFiddle Example: Mustache Directive for AngularJS

Posted At : August 7, 2014 9:13 AM | Posted By : Jon Hartmann

Related Categories: Templating, AngularJS, Examples & Tutorials, Javascript

In the blog post [Considering Speed and Slowness in AngularJS](#), the idea is put forward to use MustacheJS, wrapped in an AngularJS Directive to render dynamic content, but come away with no or minimal bindings. I liked the idea, but I found the application too specific; while I get the philosophy of making Directives specific usage, I also hate redundant tools and making a separate directive for each and every place I want to use a Mustache template seems terrible too.

The key detail to note in this example is that the first element wrapped by my directive is a div with a `ng-non-bindable` on it. That is necessary to keep AngularJS from trying to parse and bind your Mustache template code.

[Edit in JSFiddle](#)

- [JavaScript](#)
- [HTML](#)
- [Result](#)
- [Resources](#)

```
var myApp = angular.module('DemoApp', []);

myApp.directive('jnhMustache', [function () {
  var declaration = {};

  declaration.restrict = 'E';

  declaration.scope = {
    data : '&',
    watch : '='
  };

  declaration.transclude = false;

  declaration.link = function (scope, element, attrs) {
    function render () {
      var html = Mustache.render(scope.template, scope.d
```